

# 313344

**12526**

**3 Hours / 70 Marks**

Seat No. 

|  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|

---

- Instructions* –
- (1) All Questions are *Compulsory*.
  - (2) Answer each next main Question on a new page.
  - (3) Illustrate your answer with neat sketches wherever necessary.
  - (4) Figures to the right indicate full marks.
  - (5) Assume suitable data, if necessary.
  - (6) Use of Non-programmable Electronic Pocket Calculator is permissible.
  - (7) Mobile Phone, Pager and any other Electronic Communication devices are not permissible in Examination Hall.

**Marks**

- 1. Attempt any FIVE of the following: **10****
- a) Define woolen count.
  - b) Define ‘Z’ twist with suitable sketch.
  - c) Define the term ‘fabric thickness’.
  - d) Define the term ‘abrasion’.
  - e) Define the term ‘air-resistance’.
  - f) Calculate the single yarn strength in terms of tenacity (gm/tex) if breaking strength of 30 tex yarn is 275 gmf.
  - g) Calculate count strength product for 40 Ne p/c blended yarn having 80 lbs of lea strength.

P.T.O.

- 2. Attempt any THREE of the following: 12**
- Explain the ratings for assessment of water repellency by spray test.
  - Give the ratings for pilling resistance assessment of fabric.
  - Explain the method for measurement of fabric width.
  - Compare metric yarn number with denier yarn number.
- 3. Attempt any THREE of the following: 12**
- Compare constant rate of loading with constant rate of extension principle.
  - Calculate the drape coefficient for cotton dhoti from following particulars,  
Draped pattern paper weight (w) = 2.63 grams.  
Paper weight (w) = 0.012 grams/sq. cm.  
Specimen Area (As) = 491 square cm.  
Supporting disc Area (Asd) = 123 square m.
  - List the end points for assessment of abrasion resistance of the fabric.
  - Calculate cloth cover factor from the following parameters.  
EPI = 120, PPI = 60  
Warp Count = 32  
Weft Count = 32.
- 4. Attempt any THREE of the following: 12**
- Describe the procedure for measurement of bursting strength for parachute fabric with suitable diagram.
  - Explain strain gauge principle.
  - Calculate the percentage loss in thickness for denim fabric whose 0.55 mm thickness becomes 0.52 mm after 300 numbers of multidirection abrasion cycles against rock material.
  - Describe the procedure for measurement of amount of twist in single yarn with suitable diagram.
  - Describe the procedure for measurement of crease recovery angle with suitable diagram.

**5. Attempt any TWO of the following:****12**

- a) Explain random and periodic variations.
- b) Calculate fabric weight in grams per square meter from following data,

$$\text{EPI} = 120, \quad \text{PPI} = 60$$

$$\text{Warp Count} = 32$$

$$\text{Weft Count} = 32$$

$$\text{Warp Crimp} = 8\%$$

$$\text{Weft Crimp} = 7\%.$$

- c) Describe procedure for measurement of count strength procedure for cotton yarn.

**6. Attempt any TWO of the following:****12**

- a) Convert six Tex into English and metric count.
- b) Calculate bending modulus of the fabric from following data,

$$\text{Bending length (c)} = 2.34 \text{ cm.}$$

$$\text{Fabric weight (w)} = 120 \text{ mg / sqare cm.}$$

$$\text{Fabric Thickness (g)} = 0.038 \text{ cm.}$$

- c) Describe procedure for measurement of tensile strength for laminated fabric by cut-strip method.
-